

REFERENCE UNIT

CALREF 0



KEY FEATURES

- ✓ 0°C Thermoelectric reference unit
- ✓ Eliminates Old Fashioned “Ice Bath”
- ✓ Versatile use in industries, Laboratories, Instrument shop
- ✓ NABL Traceable Calibration Available

SPECIFICATIONS

Reference Junction Temp. :	0°C(Standard)
Types of T/C	: J, K, T, E, N, R, S, B
Accuracy	: ±0.1°C, Errors can be compensated by adjusting controller setting
Stability	: ±0.03°C
Stabilization Time	: 15 Mins
Capacity	: 20 No (User Defined)
Resolution	: ±0.01°C
Dimension	: 315(H) x 305(W) x 332(D)mm
Weight	: 13Kgs
Power Supply	: 230 VAC, 50 Hz
Carry Case	: Aluminium modular box

CALREF 60



KEY FEATURES

- ✓ 60°C Thermoelectric reference unit
- ✓ Versatile use in factory, Laboratory, Instrument Shop
- ✓ Rugged Outer case for safe Portability
- ✓ NABL Traceable Calibration Available

SPECIFICATIONS

Temperature Range :	+10 to 90
Types of T/C	: J, K, T, E, N, R, S, B
Accuracy	: ±0.5°C, Errors can be compensated by adjusting controller setting
Stability	: ±0.05°C
Stabilization Time	: 10 Mins
Capacity	: 6-24 Channel (User Defined)
Max. Capacity	: 48 Channel
Resolution	: ±0.1°C
Dimension(CRCA)	: 350(H)x350(W)x210(D) mm
Dimension(FRP)	: 330(H)x330(W)x180(D) mm
Weight	: 15Kg(CRCA), 10Kg(FRP)
Power Supply	: 230 V AC, 50/60 Hz / 24 V DC