


# ALUMINIUM POT THERMOCOUPLE

**T-955**



**Thermocouple Element**

Type of T/C	Description
K	Chromal/Alumal
J	Iron/Constantan
N	Nicrosil-Nisil
T	Copper/Constantan
E	Ni-Cr/Constantan
Other	Consult Factory
Ex. :	If Simplex - K Duplex - KK

**Element Wire dia**

**Junction Style**

GN	Grounded
UN	Ungrounded

**Ceramic Beads**

CERAMIC BEADS	BEADS DIA ODxH-DIA	MATERIAL
2.8x0.8-610	Ø2.8xØ0.8mm	Ceramic 610
5.5x1.2-610	Ø5.5xØ1.2mm	Ceramic 610
8.5x1.5-610	Ø8.5xØ1.5mm	Ceramic 610
5.5x1.1-610	Ø5.5xØ1.1mm	Ceramic 610
11.8x4.5-610	Ø11.8xØ4.5mm	Ceramic 610
Other: Consult Factory		

**Thermowell OD X ID :**

**Thermowell Material**

A	SS 316
B	SS 310
C	SS 304
D	Inconel-600
E	Inconel-800
F	HRS-446
Other	Consult Factory

**Cable**

A	Teflon/Teflon Insulated Flexible Cable
B	Teflon Insulated & SS Braided Flexible Cable
C	FG/FG Insulated Flexible Cable
D	PVC/PVC Insulated Flexible Cable
E	FG/FG/Insulated/SS Braided
Other	Consult Factory

**Nominal Length of T/C (L) (mm)**